

type number	A (mm)	H (mm)	B (mm)	C (mm)	thickness of metal sheet (mm)	weight (kg/ks)	🔥
NVT 62_S	62	12	222	379	0,55	0,20	🔥
NVT 62_F					0,6	0,26	🔥
NVT 125_S	125	12	285	442	0,55	0,38	🔥
NVT 125_F					0,8	0,65	🔥
NVT 250_S	250	12	410	567	0,55	0,85	🔥
NVT 250_S					0,8	1,45	🔥
NVT 500_S	500	15	660	817	0,7	2,85	🔥
NVT 500_F					0,8	3,84	🔥



product description: This cover is used to cover the T-piece NT.
To fix the cover use cover fixtures VU.
These items can also be ordered in a varnished version.

surface finish: S - Pre-Galvanized according to EN 10346, EN 10143, zinc-layer 15-27 µm
F - Hot Dip Galvanized according to ČSN EN ISO 1461, zinc-layer 45 µm (min. 35 µm)

sales amount: á 1 pc

meets the requirements: ČSN EN 61537:02

classification 🔥: ČSN 73 0895 P 90-R
DIN 4102-12 E 90
STN 92 0205 PS 90
Fire classification depends on the specific conditions of the cable tray, detailed in the catalog Systems with maintained functionality in fire.
🔥 products are approved for non-standard constructions

storage: ČSN EN 60721-3-1

